

**EUROCONTROL Specification
for Surveillance Data Exchange
ASTERIX Part 26 Category 025
CNS/ATM Ground System
Status Reports**

DOCUMENT IDENTIFIER : EUROCONTROL-SPEC-0149-26

| | | |
|-----------------------|---|----------------------------------|
| Edition Number | : | 1.1 |
| Edition Date | : | 09/11/2015 |
| Status | : | Released Edition |
| Intended for | : | General Public |
| Category | : | EUROCONTROL Specification |

DOCUMENT CHARACTERISTICS

| TITLE | | | |
|--|-----------------|-------------------|-----|
| EUROCONTROL Specification for Surveillance Data Exchange – ASTERIX Part 26 Category 025: CNS/ATM Ground System Status Reports | | | |
| Publications Reference: | | SPEC-0149-26 | |
| ISBN Number: | | 978-2-87497-028-3 | |
| Document Identifier | Edition Number: | 1.1 | |
| EUROCONTROL-SPEC-0149-26 | Edition Date: | 09/11/2015 | |
| Abstract | | | |
| This document specifies the contents of ASTERIX Category 025 reports for the transmission of the status of CNS/ATM Ground Systems. | | | |
| Keywords | | | |
| Data Exchange | Messages | SAC | SIC |
| Data Category | Data Field | Data Item | UAP |
| ASTERIX | | | |
| Contact Person(s) | Tel | Unit | |
| Alexander Engel | +32-2-729 3355 | DPS/STAN | |

| STATUS, AUDIENCE AND ACCESSIBILITY | | | | | |
|------------------------------------|-------------------------------------|----------------|-------------------------------------|--------------------------------|-------------------------------------|
| Status | | Intended for | | Accessible via | |
| Working Draft | <input type="checkbox"/> | General Public | <input checked="" type="checkbox"/> | Intranet | <input type="checkbox"/> |
| Draft | <input type="checkbox"/> | EUROCONTROL | <input type="checkbox"/> | Extranet | <input type="checkbox"/> |
| Proposed Issue | <input type="checkbox"/> | Restricted | <input type="checkbox"/> | Internet (www.eurocontrol.int) | <input checked="" type="checkbox"/> |
| Released Issue | <input checked="" type="checkbox"/> | | | | |

DOCUMENT APPROVAL

This document has been approved by the ASTERIX Maintenance Group (AMG).

For management approval of the complete set of ASTERIX documentation refer to Part 1.

DOCUMENT CHANGE RECORD

The following table records the complete history of the successive editions of the present document.

| EDITION | DATE | REASON FOR CHANGE | SECTIONS PAGES AFFECTED |
|---------|----------------|---|-------------------------------|
| 0.1 | April 2013 | First draft of a proposed new category to cover the status reporting for surveillance ground systems of various techniques. | ALL |
| 0.2 | September 2013 | Internal Review | ALL |
| 0.3 | November 2013 | Review following WG-51/SG-4 Meeting | ALL |
| 0.4 | May 2014 | Development Meeting 23.05.2014 | ALL |
| 0.5 | January 2015 | Input to EUROCAE WG-51/SG4 February 2015 | ALL |
| 1.0 | September 2015 | Data Item I025/015 reduced to 1 octet | 5.2.3 |
| 1.1 | November 2015 | Correction in bit numbering of data item I025/105 | 5.2.7 |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

Publications

EUROCONTROL Headquarters
96 Rue de la Fusée
B-1130 BRUSSELS

Tel: +32 (0)2 729 4715
Fax: +32 (0)2 729 5149
E-mail: publications@eurocontrol.int

TABLE OF CONTENTS

| | |
|--|------------|
| DOCUMENT CHARACTERISTICS | ii |
| DOCUMENT APPROVAL | iii |
| DOCUMENT CHANGE RECORD | iv |
| 1. INTRODUCTION | 1 |
| 1.1 Scope 1 | |
| 2. REFERENCES | 3 |
| 2.1 General | 3 |
| 2.2 Reference Documents | 3 |
| 3. DEFINITIONS, ACRONYMS AND ABBREVIATIONS | 5 |
| 3.1 Definitions | 5 |
| 3.2 Acronyms and Abbreviations | 6 |
| 4. GENERAL PRINCIPLES | 7 |
| 4.1 General | 7 |
| 4.2 Time Management | 7 |
| 4.3 Unused Bits in Data Items..... | 7 |
| 4.4 Definitions and Addressing Concepts | 8 |
| 4.4.1 Addressing Concepts: Assigning SAC/SIC Codes | 8 |
| 4.5 Ground System Status Reports | 8 |
| 4.5.1 Types of Ground System Status Reports | 8 |
| 4.5.2 Report Composition | 9 |
| 4.6 Composition of Reports | 9 |
| 4.6.1 Sequence of Data Items..... | 9 |
| 4.6.2 Presence of Data Items..... | 9 |
| 5. LAYOUT OF CNS/ATM GROUND SYSTEM STATUS REPORTS | 10 |
| 5.1 Standard Data Items | 10 |
| 5.2 Description of Standard Data Items | 11 |
| 5.2.1 Data Item I025/000, Report Type | 11 |
| 5.2.2 Data Item I025/010, Data Source Identifier | 13 |
| 5.2.3 Data Item I025/015, Service Identification | 13 |
| 5.2.4 Data Item I025/020, Service Designator..... | 14 |
| 5.2.5 Data Item I025/070, Time of Day..... | 16 |
| 5.2.6 Data Item I025/100, System and Service Status | 17 |
| 5.2.7 Data Item I025/105, System and Service Error Codes | 18 |
| 5.2.8 Data Item I025/120, Component Status | 20 |
| 5.2.9 Data Item I025/140, Service Statistics..... | 21 |

| | |
|--|-----------|
| 5.2.10 Data Item I025/200 Message Identification | 23 |
| 5.3 Standard User Application Profile | 24 |

This page is intentionally left blank

1. INTRODUCTION

1.1 Scope

- 1.1.1** This document describes the structure and contents of ASTERIX records for the transmission of status reports from a CNS/ATM Ground System. This term is used to cover a multitude of ground systems, that may provide differing types of service applying various techniques.

This page is intentionally left blank

2. REFERENCES

2.1 General

The following Documents and Standards contain provisions which, through references in this text, constitute provisions of this EUROCONTROL Specification.

At the time of publication of this EUROCONTROL Specification, the editions indicated for the referenced documents and standards were valid.

Any revision of referenced ICAO Documents shall be immediately taken into account to revise this EUROCONTROL Specification.

Revisions of the other referenced documents shall not form part of the provisions of this EUROCONTROL Specification until they are formally reviewed and incorporated into this EUROCONTROL Specification.

In the case of a conflict between the requirements of this EUROCONTROL Specification and the contents of the other referenced documents, this EUROCONTROL Specification shall take precedence.

2.2 Reference Documents

1. EUROCONTROL Specification SPEC-0149, edition 2.2, 17 October 2014 "EUROCONTROL Specification for Surveillance Data Exchange – Part 1 All Purpose Structured EUROCONTROL Surveillance Information Exchange – ASTERIX".

This page is intentionally left blank

3. DEFINITIONS, ACRONYMS AND ABBREVIATIONS

3.1 Definitions

For the purposes of this EUROCONTROL Specification, the following definitions shall apply:

- | | | |
|--------------|----------------------------------|---|
| 3.1.1 | Catalogue of Data Items: | List of all the possible Data Items of each Data Category describing the Data Items by their reference, structure, size and units (where applicable). |
| 3.1.3 | Data Category: | Classification of the data in order to permit inter alia an easy identification. |
| 3.1.4 | Data Field: | Physical implementation for the purpose of communication of a Data Item, it is associated with a unique Field Reference Number and is the smallest unit of transmitted information. |
| 3.1.5 | Data Item: | The smallest unit of information in each Data Category. |
| 3.1.6 | Record: | A collection of transmitted Data Fields of the same Category preceded by a Field Specification field, signalling the presence/absence of the various Data Fields. |
| 3.1.7 | User Application Profile: | The mechanism for assigning Data Items to Data Fields, and containing all necessary information which needs to be standardised for the successful encoding and decoding of the reports. |

3.2 Acronyms and Abbreviations

For the purposes of this EUROCONTROL Specification the following shall apply:

| | |
|----------------|--|
| ADS-B | Automatic Dependent Surveillance - Broadcast |
| AMG | ASTERIX Maintenance Group |
| ASTERIX | All purpose STructured Eurocontrol suRveillance Information eXchange |
| CAT | Data Category |
| FRN | Field Reference Number |
| FSPEC | Field Specification |
| FX | Field Extension Indicator |
| ICAO | International Civil Aviation Organization |
| ICD | Interface Control Document |
| LEN | Length Indicator |
| LSB | Least Significant Bit |
| NM | Nautical Mile, unit of distance (1852 metres) |
| REP | Field Repetition Indicator |
| s | second, unit of time |
| SAC | System Area Code |
| SIC | System Identification Code |
| SP | Special Purpose Indicator |
| UAP | User Application Profile (see Definitions) |
| UTC | Co-ordinated Universal Time |

4. GENERAL PRINCIPLES

4.1 General

This document describes the application of ASTERIX to CNS/ATM Ground System Status Reports.

4.2 Time Management

The time stamping shall comply with the Coordinated Universal Time (UTC) as specified in ICAO Annex 5.

4.3 Unused Bits in Data Items.

Decoders of ASTERIX data **shall never assume and rely on** specific settings of spare or unused bits. However in order to improve the readability of binary dumps of ASTERIX records, it is recommended to set all spare bits to zero.

4.4 Definitions and Addressing Concepts

4.4.1 Addressing Concepts: Assigning SAC/SIC Codes

By convention a dedicated and unambiguous SAC/SIC code shall be assigned to every Ground System Service.

4.5 Ground System Status Reports

4.5.1 Types of Ground System Status Reports

Three types of service reports have been identified:

- Service and System Status Report (Message Type 001)
- Component Status Report (Message Type 002)
- Service Statistics Report (Message Type 003)

4.5.1.1 *Service and System Status Report*

These reports **shall** convey the status of individual services provided by the ground system as well as the individual components of the system that support the service. Each ground system may provide several services, and the status of each service **shall** be reported independently in each service status report.

4.5.1.2 *Component Status Report*

These reports **shall** be sent to signal the status of individual components independent from their use in a service. The component is identified by its Component ID (data item I025/120) and it is up to the receiving system to properly interpret this number. It is up to the management of the receiving system to determine the impact of a component failure.

4.5.1.3 *Service Statistics Report*

These reports **shall** be sent to provide statistical information about an identified service.

4.5.1.4 *Message Generation Principles*

Message Types 001 and 002 **shall** be generated periodically and optionally whenever a change of the status happens. The generation of the different message types **shall** be agreed between the communication partners and **shall** be described in the system's Interface Control Document (ICD).

The generation of message type 003 **shall** be agreed between the communication partners.

4.5.2 Report Composition

A single UAP has been standardised and shall be used to transmit service reports from a Ground System to user systems.

The composition of reports of Category 025 follows the principle according to Part 1 of ASTERIX edition 2.2 or later. Each report is composed according to the following principle:

| CAT = 025 | LEN | FSPEC | DATA ITEM | DATA ITEM | DATA ITEM | ... |
|-----------|-----|-------|-----------|-----------|-----------|-----|
|-----------|-----|-------|-----------|-----------|-----------|-----|

Where:

- CAT = 025 is a one-octet field indicating Ground System Status reports;
- LEN is a two-octet field indicating the total length in octets of the Category 025 report, including the CAT and LEN fields;
- FSPEC is the Field Specification.

4.6 Composition of Reports

4.6.1 Sequence of Data Items

Reports shall be composed of Data Items assembled in the order defined by the Field Reference Number (FRN) in the associated UAP.

4.6.2 Presence of Data Items

When sent, items shall always be transmitted in a Record with the corresponding FSPEC bits set to one.

5. LAYOUT OF CNS/ATM GROUND SYSTEM STATUS REPORTS

5.1 Standard Data Items

The standardised Data Items which shall be used for the transmission of CNS/ATM Ground System Status reports are defined in Table 1 and described in the following pages.

Table 1 - Standard Data Items of Category 025

| Data Item Ref. No. | Description | System Resolution |
|---------------------------|--------------------------------|--------------------------|
| I025/000 | Report Type | N.A. |
| I025/010 | Data Source Identifier | N.A. |
| I025/015 | Service Identification | N.A. |
| I025/020 | Service Designator | N.A. |
| I025/070 | Time of Day | 1/128 s |
| I025/100 | System and Service Status | N.A. |
| I025/105 | System and Service Error Codes | N.A. |
| I025/120 | Component Status | N.A. |
| I025/140 | Service Statistics | N.A. |
| I025/200 | Message Identification | N.A. |

5.2 Description of Standard Data Items

5.2.1 Data Item I025/000, Report Type

Definition : This Data Item allows for a more convenient handling of the reports at the receiver side by further defining the type of transaction.

Format : One-octet fixed length Data Item.

Structure:

| Octet no. 1 | | | | | | | |
|-------------|---|---|---|---|---|---|----|
| 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Report Type | | | | | | | RG |

bits-8/2

Report Type

bit-1

Cat 025 Report Generation

=0: Periodic Report

=1: Event Driven Report

NOTES

1. In applications where transactions of various types are exchanged, the Report Type Data Item facilitates the proper report handling at the receiver side.
2. All Report Type values are reserved for common standard use.
3. The following set of Report Types are standardised for Category 025 records:
 - 001 Service and System Status report (see [4.5.1.1.](#) above)
 - 002 Component Status report (see [4.5.1.2.](#) above)
 - 003 Service Statistics report (see [4.5.1.3.](#) above)
4. The list of items present for the three report types is defined in the following table.
M stands for mandatory, O for optional, X for never present.

Table 2 - Report Types


| Type Item | 001 Service and System Status | 002 Component Status | 003 Service Statistics |
|--|-------------------------------------|----------------------------|------------------------------|
| I025/000 Report Type | M | M | M |
| I025/010 Data Source Identifier | M | M | M |
| I025/015 Service Identification | M | X | M |
| I025/020 Service Designator | O | X | O |
| I025/070 Time of Day | M | M | M |
| I025/100 System & Service Status | O | X | X |
| I025/105 Service Error Codes | O | X | X |
| I025/120 Component Status | O | M | X |
| I025/140 Service Statistics | X | X | M |
| I025/200 Message Identification | O | O | O |

5.2.2 Data Item I025/010, Data Source Identifier

Definition : Identification of the Ground System from which the data is received.

Format : Two-octet fixed length Data Item.

Structure:



NOTE - The up-to-date list of SACs is published on the EUROCONTROL Web Site (<http://www.eurocontrol.int/asterix>).


NOTE - The SICs are allocated by the national authority responsible for the surveillance infrastructure.

5.2.3 Data Item I025/015, Service Identification

Definition : Identifies the service being reported.

Format : One-octet fixed length Data Item.

Structure:



bits-8/1 (SID) Service Identification

Note: The service identification is allocated by the system.

5.2.4 Data Item I025/020, Service Designator**Definition :** Designator of the service being reported.**Format :** Six-octet fixed length Data Item.**Structure:**

| Octet no. 1 | | | | | | | | Octet no. 2 | | | | | | | |
|-------------|----|----|----|----|----|-------------|----|-------------|----|----|----|-------------|----|----|----|
| 48 | 47 | 46 | 45 | 44 | 43 | 42 | 41 | 40 | 39 | 38 | 37 | 36 | 35 | 34 | 33 |
| Character 1 | | | | | | Character 2 | | | | | | Character 3 | | | |

| Octet no. 3 | | | | | | | | Octet no. 4 | | | | | | | |
|-------------|----|-------------|----|----|----|----|----|-------------|----|----|----|----|----|----|----|
| 32 | 31 | 30 | 29 | 28 | 27 | 26 | 25 | 24 | 23 | 22 | 21 | 20 | 19 | 18 | 17 |
| | | Character 4 | | | | | | Character 5 | | | | | | | |

| Octet no. 5 | | | | | | | | | | Octet no. 6 | | | | | |
|-------------|----|----|----|-------------|----|----|---|---|---|-------------|---|---|---|---|---|
| 16 | 15 | 14 | 13 | 12 | 11 | 10 | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Character 6 | | | | Character 7 | | | | | | Character 8 | | | | | |

bits-48/1 Service Designator. Characters 1-8 (coded on 6 Bits each) defining the text readable designator for each Service.

Each character of the service designator is encoded as defined below (see ICAO Annex 10, Volume IV, page 3-77, table 3-9):

| | | | | | | | | |
|----------------|----------------|----------------|----------------|----------------|---|---|-----------------|---|
| | | | | b ₆ | 0 | 0 | 1 | 1 |
| | | | | b ₅ | 0 | 1 | 0 | 1 |
| b ₄ | b ₃ | b ₂ | b ₁ | | | | | |
| 0 | 0 | 0 | 0 | | | P | SP ¹ | 0 |
| 0 | 0 | 0 | 1 | | A | Q | | 1 |
| 0 | 0 | 1 | 0 | | B | R | | 2 |
| 0 | 0 | 1 | 1 | | C | S | | 3 |
| 0 | 1 | 0 | 0 | | D | T | | 4 |
| 0 | 1 | 0 | 1 | | E | U | | 5 |
| 0 | 1 | 1 | 0 | | F | V | | 6 |
| 0 | 1 | 1 | 1 | | G | W | | 7 |
| 1 | 0 | 0 | 0 | | H | X | | 8 |
| 1 | 0 | 0 | 1 | | I | Y | | 9 |
| 1 | 0 | 1 | 0 | | J | Z | | |
| 1 | 0 | 1 | 1 | | K | | | |
| 1 | 1 | 0 | 0 | | L | | | |
| 1 | 1 | 0 | 1 | | M | | | |
| 1 | 1 | 1 | 0 | | N | | | |
| 1 | 1 | 1 | 1 | | O | | | |

SP¹ = SPACE code

For each character the following bit numbering convention shall be observed:

| | | | | | |
|----|----|----|----|----|----|
| b6 | b5 | b4 | b3 | b2 | b1 |
|----|----|----|----|----|----|

Notes:

1. Assignments of Service designators to specific services/systems and interpretation of these fields are implementation dependent.
2. Examples of Service Designators are "1090ADSB", "WAM", "1090TISB", etc.
3. Multiple Service Type Designators may be used to describe a single service where applicable

5.2.5 Data Item I025/070, Time of Day**Definition :** Absolute time stamping expressed as UTC time.**Format :** Three-octet fixed length Data Item.**Structure:**

| Octet no. 1 | | | | | | | |
|-------------|----|----|----|----|----|----|----|
| 24 | 23 | 22 | 21 | 20 | 19 | 18 | 17 |
| TIME | | | | | | | |

| Octet no. 2 | | | | | | | | Octet no. 3 | | | | | | | |
|-------------|----|----|----|----|----|----|---|-------------|---|---|---|---|---|---|-----|
| 16 | 15 | 14 | 13 | 12 | 11 | 10 | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| OF DAY | | | | | | | | | | | | | | | LSB |

bit-1 (LSB) = $(2^{-7})s$ = 1/128 s

NOTES

1. The time of day value is reset to zero each day at midnight.

5.2.6 Data Item I025/100, System and Service Status

Definition : Information concerning the status of the Service Volume.

Format : A one octet extensible field.

Structure:

| Octet no. 1 | | | | | | | |
|-------------|-----|---|-------|---|---|---|----|
| 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| NOGO | OPS | | SSTAT | | | | FX |

| | | |
|----------|---------|---|
| bit-8 | (NOGO) | Operational Release Status of the Data = 0 Data is released for operational use = 1 Data must not be used operationally |
| bit-7/6 | (OPS) | Operational Service Mode = 0 Operational = 1 Operational but in Standby = 2 Maintenance = 3 reserved for future use |
| bits-5/2 | (SSTAT) | System and Service State = 0 Running = 1 Failed = 2 Degraded = 3 Undefined = 4 – 15 reserved for future use |
| bit-1 | (FX) | = 0 No extension = 1 Extension |

NOTES



1. Bit 8 (NOGO), when set to “1” indicates that the data transmitted by the system/service is not released for operational use. This indication is independent from the status of the system itself or that of the service. It just indicates that the system or service volume output **must not** be used for operational services but may be used for, e.g. test and validation purposes. The indication GO/NO-GO indicates a mode of the system rather than a status. Usually this bit will be set by operator input.
2. Bit 7/6 (OPS), when set to “1” indicates that the system is running but not operationally used (e.g. for a standby system in a redundant configuration).
3. Bits 5/2 (SSTAT): This information informs about the state of the overall service volume status. The actual implementation of this field is service dependent and should be described in the system/service specification. However, it is expected that – as far as this information is available – a mapping is performed between the states of individual components as reported in data item I025/120. As an example, if one component fails but the system is still operational (at least partially), the service status should change to “degraded”.

5.2.7 Data Item I025/105, System and Service Error Codes

Definition : Error Status of the System and the Service.

Format : Repetitive Data Item, starting with a one-octet Field Repetition Indicator (REP) followed by at least one error code of 1 octet.

Structure:



NOTES:

The Warning & Error codes contain information about the reason why the System and Service State (SSTAT in item I025/100) is different from “running”.

In this edition of the specification, the following warning & error codes are defined:

| Error Code | Meaning |
|------------|---|
| 0 | No error detected (shall not be sent) |
| 1 | Error Code Undefined |
| 2 | Time Source Invalid |
| 3 | Time Source Coasting |
| 4 | Track ID numbering has restarted |
| 5 | Data Processor Overload |
| 6 | Ground Interface Data Communications Overload |
| 7 | System stopped by operator |
| 8 | CBIT failed |
| 9 | Test Target Failure |
| 10 – 31 | Reserved for allocation by the AMG |
| 32 - 255 | Reserved for allocation by system manufacturers |

- 1 A time source is considered as valid when either externally synchronised or running on a local oscillator within the required accuracy of UTC.
2. A value of 4 indicates that the allocation of Track-IDs was re-started.
3. Multiple error codes can be transmitted within the same ASTERIX record.


4. Error codes in the range 0 to 31 shall be allocated centrally by the AMG. Error codes in the range from 32 to 255 are available for specification by the system manufacturers. They are not standardised and shall be described in the Interface Control Document (ICD) of the respective system.

5.2.8 Data Item I025/120, Component Status

Definition: Indications of status of various system components and, when applicable, error codes.

Format : Repetitive Data Item, starting with a one-octet Field Repetition Indicator (REP) followed by at least one block of 3 octets.

Structure:




bits-32/25 (REP) Number of Component Status Reports

bits-24/9 (CID) Component ID

The Component ID is implementation specific

A Component ID of 65535 indicates that the following error code applies to **all** components defined.



Bits-8/3 (Error Code) 0: No Error Detected
 1: Error Code Undefined
 2-15 Reserved for allocation by the AMG
 16-63 Reserved for allocation by system manufacturers

bits-2/1 (CS) Component State
 =0: Running
 =1: Failed
 =2: Maintenance
 =3: reserved

NOTES:

Error codes in the range 2 to 15 shall be allocated centrally by the AMG. Error codes in the range from 16 to 63 are available for specification by the system manufacturers. They are not standardised and shall be described in the Interface Control Document (ICD) of the respective system.

5.2.9 Data Item I025/140, Service Statistics

Definition : Statistics concerning the service. Provides counts of various message types that have been received since the report was last sent.

Format : Repetitive Data Item, starting with a one-octet Field Repetition Indicator (REP) followed by at least one block of 6 octets.

Structure:

| Octet no. 1 | | | | | | | |
|-------------|----|----|----|----|----|----|----|
| 56 | 55 | 54 | 53 | 52 | 51 | 50 | 49 |
| REP | | | | | | | |

| Octet no. 2 | | | | | | | | Octet no. 3 | | | | | | | |
|-------------|----|----|----|----|----|----|----|-------------|-------|----|----|----|----|----|----|
| 48 | 47 | 46 | 45 | 44 | 43 | 42 | 41 | 40 | 39 | 38 | 37 | 36 | 35 | 34 | 33 |
| TYPE | | | | | | | | REF | SPARE | | | | | | |

| Octet no. 4 | | | | | | | | Octet no. 5 | | | | | | | |
|---------------|----|----|----|----|----|----|----|-------------|----|----|----|----|----|----|----|
| 32 | 31 | 30 | 29 | 28 | 27 | 26 | 25 | 24 | 23 | 22 | 21 | 20 | 19 | 18 | 17 |
| COUNTER VALUE | | | | | | | | | | | | | | | |

| Octet no. 6 | | | | | | | | Octet no. 7 | | | | | | | |
|---------------|----|----|----|----|----|----|---|-------------|---|---|---|---|---|---|---|
| 16 | 15 | 14 | 13 | 12 | 11 | 10 | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| COUNTER VALUE | | | | | | | | | | | | | | | |

| | | |
|------------|--------|---|
| bits-56/49 | (REP) | Number of counters following |
| bits-48/41 | (TYPE) | Type of report counter, encoded as follows |
| | | = 0 Number of unknown messages received |
| | | = 1 Number of 'too old' messages received |
| | | = 2 Number of failed message conversions |
| | | = 3 Total Number of messages received |
| | | = 4 Total number of messages transmitted |
| | | = 5-19 Reserved for AMG |
| | | ≥ 20 implementation specific |
| bit-40 | (REF) | Reference from which the messages are counted |
| | | = 0 From UTC midnight |
| | | = 1 From the previous report |

| | | |
|------------|--------------------|----------------------|
| bits-39/33 | (SPARE) | Spare bits set to 0 |
| bits-32/1 | (COUNTER VALUE) | 32-bit counter value |

Notes:

There is no special significance attributed to the numbering of the TYPE field. However the range from 0 to 19 is intended to cover generic messages which may be applicable to many types of service.

5.2.10 Data Item I025/200 Message Identification

Definition: Identification of a unique message.

Format: Three-octet fixed length Data Item.

Structure:

| Octet 1 | | | | | | | | | | Octet 2 | | | | | |
|-------------------------------|----|----|----|----|----|----|----|----|----|---------|----|----|----|----|---|
| 24 | 23 | 22 | 21 | 20 | 19 | 18 | 17 | 16 | 15 | 14 | 13 | 12 | 11 | 10 | 9 |
| Message Identification Number | | | | | | | | | | | | | | | |

| Octet 3 | | | | | | | |
|--------------------------------------|---|---|---|---|---|---|---|
| 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Message Identification Number (cont) | | | | | | | |

bits-24/1

Message Identification Number

Notes:

1. The Message Identification Number is to be used to uniquely identify each message. If messages are being sent on redundant links then this number shall be identical for the same message on each link. This will allow the receiver to easily identify and discard duplicate messages.
2. It is not required that Message Identification Numbers be assigned in ascending order by time of message transmission.

5.3 Standard User Application Profile

The following standard UAP shown in Table 3 shall be used for the transmission of CNS/ATM Ground System Status reports:

Table 3 - Standard UAP for CNS/ATM Ground System Status Reports

| FRN | Data Item | Data Item Description | Length |
|-----|------------------|--------------------------------|--------|
| 1 | I025/010 | Data Source Identifier | 2 |
| 2 | I025/000 | Report Type | 1 |
| 3 | I025/200 | Message Identification | 3 |
| 4 | I025/015 | Service Identification | 1 |
| 5 | I025/020 | Service Designator | 6 |
| 6 | I025/070 | Time of Day | 3 |
| 7 | I025/100 | System and Service Status | 1+ |
| FX | N/A. | Field Extension Indicator | N/A. |
| 8 | I025/105 | System and Service Error Codes | 1+ |
| 9 | I025/120 | Component Status | 1+ |
| 10 | I025/140 | Service Statistics | 1+ |
| 11 | SP- Data Item | Special Purpose Field | 1+1+ |
| 12 | - | Spare | N/A. |
| 13 | - | Spare | N/A. |
| 14 | - | Spare | N/A. |
| FX | N/A. | Field Extension Indicator | N/A. |

where:

- the first column indicates the FRN associated to each Data Item used in the UAP;
- the fourth column gives the format and the length of each item, a stand-alone figure indicates the octet count of a fixed-length Data Item, 1+ indicates a variable-length Data Item comprising a first part of one-octet followed by n-octets extent as necessary.