

**EUROCONTROL STANDARD DOCUMENT**  
**FOR**  
**SURVEILLANCE DATA EXCHANGE**

**Part 20 : Category 247**  
**Version Number Exchange**



<b>Edition</b>	<b>:</b>	<b>1.2</b>
<b>Edition Date</b>	<b>:</b>	<b>February 2008</b>
<b>Status</b>	<b>:</b>	<b>Released Issue</b>
<b>Class</b>	<b>:</b>	<b>General Public</b>

# DOCUMENT IDENTIFICATION SHEET

## DOCUMENT DESCRIPTION

**Document Title**  
Version Number Exchange

EWP DELIVERABLE REFERENCE NUMBER

**PROGRAMME REFERENCE INDEX**

**EDITION :** 1.2

**EDITION DATE :** February 2008

### Abstract

This document describes the application of ASTERIX messages to the transmission of category version number report.

### Keywords

Data Item	ASTERIX Category 247	UAP	Version Number
-----------	-------------------------	-----	----------------

**CONTACT PERSON :** A. Engel

**TEL :** +32-2-729 3355

**DIVISION :** DAP/SUR

## DOCUMENT STATUS AND TYPE

STATUS	CATEGORY	CLASSIFICATION
Working Draft <input type="checkbox"/>	Executive Task <input type="checkbox"/>	General Public <input checked="" type="checkbox"/>
Draft <input type="checkbox"/>	Specialist Task <input type="checkbox"/>	EATCHIP <input type="checkbox"/>
Proposed Issue <input type="checkbox"/>	Lower Layer Task <input checked="" type="checkbox"/>	Restricted <input type="checkbox"/>
Released Issue <input checked="" type="checkbox"/>		

## ELECTRONIC BACKUP

**INTERNAL REFERENCE NAME :**

HOST SYSTEM	MEDIA	SOFTWARE(S)
Microsoft Windows	Type : Hard disk	
	Media Identification :	

### DOCUMENT APPROVAL

The following table identifies all management authorities who have successively approved the present issue of this document.

<b>AUTHORITY</b>	<b>NAME AND SIGNATURE</b>	<b>DATE</b>
ASTERIX Manager	D. Doukas	
SUR Domain Manager	J. Berends	
SURT Chairman	M. Rees	
EATM/DAP Director	G. Kerkhofs	

## DOCUMENT CHANGE RECORD

The following table records the complete history of the successive editions of the present document.

<b>EDITION</b>	<b>DATE</b>	<b>REASON FOR CHANGE</b>	<b>SECTIONS PAGES AFFECTED</b>
0.10	October 2005	Creation of document	All
0.11	November 2005	Title changed to "Version Number Exchange"	All
1.0	May 2007	Scope updated Document Identification Sheet updated Signature Page updated Status updated to "Released Issue"	1.1.2 ii iii All
1.1	November 2007	Category renumbered to 247 because of conflict with existing category 242	All
1.2	January 2008	Item I247/015 (Service Identification) added	5.2.2

---

## TABLE OF CONTENTS

<b>DOCUMENT IDENTIFICATION SHEET .....</b>	<b>ii</b>
<b>DOCUMENT APPROVAL.....</b>	<b>iii</b>
<b>DOCUMENT CHANGE RECORD .....</b>	<b>iv</b>
<b>TABLE OF CONTENTS.....</b>	<b>v</b>
<b>EXECUTIVE SUMMARY .....</b>	<b>1</b>
<b>1. INTRODUCTION.....</b>	<b>2</b>
<b>1.1 Scope .....</b>	<b>2</b>
<b>2. REFERENCES.....</b>	<b>3</b>
<b>2.1 General.....</b>	<b>3</b>
<b>2.2 Reference Documents .....</b>	<b>3</b>
<b>3. DEFINITIONS, ACRONYMS AND ABBREVIATIONS .....</b>	<b>5</b>
<b>3.1 Definitions.....</b>	<b>5</b>
<b>3.2 Acronyms and Abbreviations .....</b>	<b>6</b>
<b>4. GENERAL PRINCIPLES .....</b>	<b>7</b>
<b>4.1 General.....</b>	<b>7</b>
<b>4.2 Time Management.....</b>	<b>7</b>
4.2.1 Definition .....	7
4.2.2 Requirements for Time Stamping .....	7
<b>4.3 Unused Bits in Data Items.....</b>	<b>7</b>
<b>4.4 Definitions and Addressing Concepts .....</b>	<b>7</b>
4.4.1 System .....	7
4.4.2 Addressing Concepts: Assigning SAC/SIC Codes.....	7
<b>4.5 Service Messages .....</b>	<b>7</b>
<b>4.6 User Application Profile and Data Blocks .....</b>	<b>8</b>
<b>4.7 Composition of Messages.....</b>	<b>8</b>

<b>5.</b>	<b>LAYOUT OF MESSAGES .....</b>	<b>9</b>
<b>5.1</b>	<b>Standard Data Items .....</b>	<b>9</b>
<b>5.2</b>	<b>Description of Standard Data Items .....</b>	<b>10</b>
5.2.1	Data Item I247/010, Data Source Identifier .....	10
5.2.2	Data Item I247/015, Service Identification .....	10
5.2.3	Data Item I247/140, Time of Day .....	11
5.2.4	Data Item I247/550, Category Version Number Report .....	12
<b>5.3</b>	<b>Standard User Application Profile .....</b>	<b>13</b>

## **EXECUTIVE SUMMARY**

This document describes the general concepts and the message layout for the application of ASTERIX category 247 for the transmission of version number information related to the ASTERIX Categories used by a system.

## 1. INTRODUCTION

### 1.1 Scope

1.1.1 This document describes the message structure for the transmission of ASTERIX categories version number reports.

1.1.2 The use of intermediate editions of a specific ASTERIX category shall be limited to the test and development phase of a new system and/or a new ASTERIX category. As soon as the status of both is stable, the system shall be migrated to the use of the latest available version of a specific ASTERIX category.

## **2. REFERENCES**

### **2.1 General**

The following Documents and Standards contain provisions which, through references in this text, constitute provisions of this Eurocontrol Document.

At the time of publication of this Eurocontrol Document, the editions indicated for the referenced documents and standards were valid.

Any revision of the referenced ICAO Documents shall be immediately taken into account to revise this Eurocontrol Document.

Revisions of the other referenced documents shall not form part of the provisions of this Eurocontrol Document until they are formally reviewed and incorporated into this Eurocontrol Document.

In case of a conflict between the requirements of this Eurocontrol Document and the contents of the other referenced documents, this Eurocontrol Document shall take precedence.

### **2.2 Reference Documents**

1. Eurocontrol Standard 000-1-92. Directives for the Uniform Drafting and Presentation of Eurocontrol Standard Documents. 1992.
2. Eurocontrol Standard SUR.ET1.ST05.2000-STD-01-01. All Purpose Structured Eurocontrol Surveillance Information Exchange - ASTERIX. Edition 1.29, Released Issue, February 2002.
3. ICAO Annex 5

This page is intentionally left blank

### 3. DEFINITIONS, ACRONYMS AND ABBREVIATIONS

#### 3.1 Definitions

For the purposes of this Eurocontrol Document, the following definitions shall apply:

- |              |                                  |  |
|--------------|----------------------------------|--|
| <b>3.1.1</b> | <b>Catalogue of Data Items:</b>  | List of all possible Data Items of each Data Category describing the Data Items by their reference, structure, size and units (where applicable).  |
| <b>3.1.2</b> | <b>Data Block:</b>               | Unit of information seen by the application as a discrete entity by its contents. A Data Block contains one or more Record(s) containing data of the same category.                      |
| <b>3.1.3</b> | <b>Data Category:</b>            | Classification of the data in order to allow for, inter alia, an easy identification.  |
| <b>3.1.4</b> | <b>Data Field:</b>               | Physical implementation for the purpose of communication of a Data Item. It is associated with a unique Field Reference Number and is the smallest unit of transmitted information.      |
| <b>3.1.5</b> | <b>Data Item:</b>                | The smallest unit of information in each Data Category.  |
| <b>3.1.6</b> | <b>Measured Item:</b>            | A piece of information (e.g. the position of a target) derived from the sensor information and transmitted without any smoothing.  |
| <b>3.1.7</b> | <b>Record:</b>                   | A collection of transmitted Data Fields of the same category preceded by a Field Specification field, signalling the presence/absence of the various Data Fields                         |
| <b>3.1.8</b> | <b>User Application Profile:</b> | The mechanism for assigning Data Items to Data Fields, and containing all necessary information which needs to be standardised for the successful encoding and decoding of the messages. |

### 3.2 Acronyms and Abbreviations

For the purposes of this Eurocontrol Document the following shall apply:

°	Degree (angle)
<b>ASTERIX</b>	<b>All Purpose STructured Eurocontrol suRveillance Information EXchange</b>
<b>CAT</b>	Data Category
<b>EATM</b>	European Air Traffic Management
<b>FL</b>	Flight Level, unit of altitude (expressed in 100's of feet)
<b>FRN</b>	Field Reference Number
<b>FSPEC</b>	Field Specification
<b>FX</b>	Field Extension Indicator
<b>ICAO</b>	International Civil Aviation Organization
<b>kt</b>	knot = NM/hour, unit of speed
<b>LEN</b>	Length Indicator
<b>LSB</b>	Least Significant Bit
<b>MLT</b>	Multilateration
<b>NM</b>	Nautical Mile, unit of distance (1852 metres)
<b>PSR</b>	Primary Surveillance Radar
<b>RDE-FG</b>	Radar Data Exchange Focus Group
<b>RE</b>	Reserved Expansion Indicator
<b>REP</b>	Field Repetition Indicator
<b>s</b>	second, unit of time
<b>SAC</b>	System Area Code
<b>SIC</b>	System Identification Code
<b>SMR</b>	Surface Movement Radar
<b>SMS</b>	Surface Movement System
<b>SP</b>	Special Purpose Indicator
<b>SPI</b>	Special Position Identification
<b>SSR</b>	Secondary Surveillance Radar
<b>SURT</b>	Surveillance Team (EATM)
<b>UAP</b>	User Application Profile (see Definitions )
<b>UTC</b>	Coordinated Universal Time
<b>WAM</b>	Wide Area Multilateration
<b>WGS-84</b>	World Geodetic System 84

## **4. GENERAL PRINCIPLES**

### **4.1 General**

For the transmission of version number of ASTERIX categories the following types of messages have been defined:

- version number(s) report

### **4.2 Time Management**

#### **4.2.1 Definition**

The time stamp shall be consistent with the time of report transmission.

#### **4.2.2 Requirements for Time Stamping**

The timestamping shall comply with ICAO Annex 5.

### **4.3 Unused Bits in Data Items.**

Decoders of ASTERIX data shall never assume and rely on specific settings of spare or unused bits. However in order to improve the readability of binary dumps of ASTERIX records, it is recommended to set all spare bits to zero.

### **4.4 Definitions and Addressing Concepts**

In order to address sources in an unambiguous way, a simple abstract model for concepts like sensors or systems has been designed.

#### **4.4.1 System**

In the framework of category 247 a System is any device delivering ASTERIX data.

#### **4.4.2 Addressing Concepts: Assigning SAC/SIC Codes**

By convention a dedicated and unambiguous SAC/SIC code shall be assigned to every System.

### **4.5 Service Messages**

Periodic Status Messages (these messages should be used by systems to indicate their Categories version numbers periodically),

---

## 4.6 User Application Profile and Data Blocks

**4.8.1** A single User Application Profile (UAP) is defined and shall be used for both target reports and service messages.

**4.8.2** Data Blocks shall have the following layout.

<b>CAT = 247</b>	<b>LEN</b>		<b>FSPEC</b>	Items of the first record
------------------	------------	--	--------------	---------------------------

where:

- Data Category (CAT) = 247, is a one-octet field indicating that the Data Block contains Multilateration data;
- Length Indicator (LEN) is a two-octet field indicating the total length in octets of the Data Block, including the CAT and LEN fields;
- FSPEC is the Field Specification.

## 4.7 Composition of Messages

**4.9.1** Messages shall be composed of Data Items assembled in the order defined by the Field Reference Number (FRN) in the associated UAP.

**4.9.2** When sent, items shall always be transmitted in a record with the corresponding FSPEC bits set to one.

## 5. LAYOUT OF MESSAGES

### 5.1 Standard Data Items

The standardised Data Items, which shall be used for the transmission of Category Version numbers are defined in Table 1 and described on the following pages.

**Table 1 - Standard Data Items of Category 247**

<b>Data Item Ref. No.</b>	<b>Description</b>	<b>Resolution</b>
I247/010	Data Source Identifier	N.A.
I247/015	Service Identification	N.A.
I247/140	Time of Day	N.A.
I247/550	Version number(s) of CAT used	N.A.

## 5.2 Description of Standard Data Items

### 5.2.1 Data Item I247/010, Data Source Identifier

**Definition:** Identification of the system from which the data are received.

**Format:** Two-octet fixed length Data Item.

**Structure:**

Octet no. 1								Octet no. 2							
16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1
SAC								SIC							

bits-16/9 (SAC) System Area Code

bits-8/1 (SIC) System Identification Code

**Encoding Rule :** This item shall be present in each ASTERIX message

### 5.2.2 Data Item I247/015, Service Identification

**Definition :** Identification of the service provided to one or more users.

**Format :** One-Octet fixed length data item.

**Structure:**

Octet no. 1							
8	7	6	5	4	3	2	1
Service Identification							

bits 8/1 Service Identification

**NOTE -** The service identification is allocated by the system

**Encoding Rule :**  
This item is optional.



### 5.2.4 Data Item I247/550, Category Version Number Report

**Definition:** Version number of Categories used.

**Format:** Repetitive Data Item starting with a one-octet Field Repetition Indicator (REP) followed by at least one Version number report for each Category used and comprising one octet CAT number and one two octets Version Number (Main/Sub).

**Structure:**

Octet no. 1							
32	31	30	29	28	27	26	25
REP							

Octet no. 2							
24	23	22	21	20	19	18	17
CAT							

Octet no. 3								Octet no. 4							
16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1
Main version number								Sub version number							

bits-32/25	(REP)	Repetition factor
bits-24/17	CAT	ASTERIX Category [0..255]
bits-16/9	Main Version Number	[0..99] e.g Vers: 1.1
bits-8/1	Sub Version Number	[0..99] e.g Vers: 1.1

**Encoding Rule :** This item shall be present in each ASTERIX message

### 5.3 Standard User Application Profile

5.3.1 The following UAP shown in Table 3 shall be used for the transmission of reports:

**Table 3 - Standard UAP**

FRN	Data Item	Information	Length in Octets
1	I247/010	Data Source Identifier	2
2	I247/015	Service Identification	1
3	I247/140	Time of Day	3
4	I247/550	Version number report	1+3*n
5	-	Spare	-
6	SP	Special Purpose Field	-
7	RE	Reserved Expansion Field	-
FX	-	Field Extension Indicator (set to 0)	-

where:

- the first column indicates the FRN associated to each Data Item used in the UAP;
- the fourth column gives the format and the length of each item. A stand-alone figure indicates the octet count of a fixed-length Data Item, 1+ indicates a variable-length Data Item comprising a first part of one-octet followed by n-octet extents as necessary.

The maximum length of the corresponding FSPEC is one octet.