

# Lessons Learned from the Speech Recognition and Understanding project HAAWaii


Mohsan Jameel, Hartmut Helmke

Institute of Flight Guidance, German Aerospace Center (DLR)


20<sup>th</sup> April 2023



# ATCo and Pilot Voice Communication



# ATCo and Pilot Voice Communication



faroe line four five three good afternoon  
radar contact squawk two seven six two

faroe line four five three after gunpa  
cleared direct robur three eight zero



two seven sixty **one** squawk  
faroe line four five three

gunpa robur flight level three eight zero  
faroe line four five three



## Readback Errors

Readback errors are seldom events and hard to detect

14%



## Hearback Errors

Undetected readback errors are categorized as Hearback Errors


40-60%




Readback Error Detection Assistant (REDA)



# Data Driven Approach to Readback Error Detection Assistant





Voice data from  
NATS and Isavia



Generate  
Synthetic  
data

Synthetic training data



# REDA Evaluation (1/2)





Test Data: 87 readback errors / 2200 correct readbacks communications threads


	Absolute Number		Rates			
	Detected RB Errors	False Alarms	Detection	False Alarm	Accuracy	F1-Score
Data-Driven	37	133	43%	78%	92%	29%

Improve automation model ➔ Need Ops room data at large scale

# Rule-Based Approach to Readback Error Detection Assistant



Ontology developed in SESAR PJ.16-04 by a consortium of European partners



FLI453 GREETING  
FLI453 INIT\_RESPONSE  
FLI453 SQUAWK 2762

faroe line four five three good afternoon  
radar contact squawk two seven six two



FLI453 SQUAWK 2761

two seven sixty one squawk  
faroe line four five three

## REDA Evaluation (2/2)



Test Data: 87 readback errors / 2200 correct readbacks communications threads

	Absolute Number		Rates			
	Detected RB Errors	False Alarms	Detection	False Alarm	Accuracy	F1-Score
Data-Driven	37	133	43%	78%	92%	29%
Rule-Based	72	163	83%	69%	92%	45%
Combined	71	145	82%	67%	93%	47%

Improve automation model → Need Ops room data at large scale

REDA: 82% detection rate > Human: 40-60% detection rate

# Moving from Lab to Ops Room



- Decide on feedback about Readback errors
  - according to rules/manual → phraseology is not “always” by the book
  - brought to the controller’s attention → decide on the context
  - communicated to the pilot → decide on the type
- Show output at the supervisor position
- More data needed
  - **Test data** for offline evaluation
  - **Feedback** from the end user
  - **Actual statistics** of Readback errors (not just an approximation)




image: Flaticon.com



# HAAWAI REDA prototype in **Ops Room**

**Date:** June, 29<sup>th</sup> 2022

**Location:** Reykjavik Ops Room


**Event:** REDA connected to **real-time** voice and surveillance data



# Speech Recognition and Machine Learning Roadmap



If you are enthusiastic about supporting **ATCO's mission** through technology




DLR offers to make source code available



### Speech Recognition meets Air Traffic Control

PILOT: descending flight level one three zero easy six nine four one	EZY8941	DESCEND	130 FL	END
ATCO: easy six nine four one descend flight level one one zero	EZY8941	DESCEND	110 FL	END
ATCO: thank you good morning identified	NO_CALLSIGN	GREETING		END
PILOT: united eight zero one flight level three five zero	UAL801	ALTITUDE	350 FL	END
ATCO: calling say again	NO_CALLSIGN	SAY_AGAIN		END
PILOT: united eight zero one flight level three five zero	UAL801	ALTITUDE	350 FL	REP
ATCO: easy six nine four one reykjavik control good morning identified	EZY8941	STATION	REYK_RADAR	END
PILOT: easy six nine four one good morning reykjavik flight level two one zero which mach number zero decimal seven eight	EZY8941	GREETING		END
	EZY8941	STATION	REYK_RADAR	REP
	EZY8941	ALTITUDE	210 FL	REP
	EZY8941	SPEED	0.78 MA	END
PILOT: descending flight level two eight zero direct dexion zero five five nine	WGN0559	DESCEND	280 FL	END
	WGN0559	DIRECT_TO	DEXON	none
ATCO: western global zero five five nine descend flight level two eight zero direct to dexion	WGN0559	DESCEND	280 FL	END
	WGN0559	DIRECT_TO	DEXON	none
ATCO: western global zero five five nine reykjavik identified	WGN0559	STATION	REYK_RADAR	END
	WGN0559	INIT_RESPONSE		END

### Pilot read back wrong flight level



Readback Status

Show Recognized Flight Level Value

Immediate Callsign Highlighting