EUROPEAN ORGANISATION FOR THE SAFETY OF AIR NAVIGATION



ASTERIX Part 21 Category 007 Appendix A Coding rules for "Reserved Expansion Field"

SUR.ET1.ST05.2000-STD-14-02

Edition : 1.0
Edition Date : April 2010
Status : Released Issue
Class : General Public

DOCUMENT IDENTIFICATION SHEET

DOCUMENT DESCRIPTION								
			ent Title					
	Codi	ng rules for "Rese	erved Expar	nsion F	ield"			
EWP DELIVERABLE F	REFERENC	E NUMBER						
PROGRAMME R	REFERENC	E INDEX	EDITION	:	1.0			
			EDITION	DATE :	: April 2010			
		Λho	tract		·			
		Aus	liaci					
		V						
		Keyv	vords					
CONTACT PERSON :	A. Engel	TEL: +32-2-7	29 3355	DIVIS	SION: CND/CoE/CN/SU			
	D	OCUMENT ST	ATUS AND) TYPI	Ε			
STATUS			GORY		CLASSIFICATION			
Working Draft		Executive Tas	k		General Public	$\overline{\mathbf{V}}$		
Draft		Specialist Tas	k		EATCHIP			
Proposed Issue		Lower Layer T	Restricted					

ELECTRONIC BACKUP								
INTERNAL REFERENCE NAM	INTERNAL REFERENCE NAME :							
HOST SYSTEM	MEDIA	SOFTWARE(S)						
Microsoft Windows	Type : Hard disk							
	Media Identification :							

Released Issue

DOCUMENT APPROVAL

The following table identifies all management authorities who have successively approved the present issue of this document.

AUTHORITY	NAME AND SIGNATURE	DATE
ASTERIX		
Manager	D. Doukas	
SUR Domain		
Manager	JM. Duflot	
SURT		
Chairman	Pending	
CND		
Director	B. Redeborn	

DOCUMENT CHANGE RECORD

The following table records the complete history of the successive editions of the present document.

EDITION	DATE	REASON FOR CHANGE	SECTIONS PAGES AFFECTED
0.1	February 2010	Creation	All
0.2	March 2010	Definition and Note to TA item updated	2.3
1.0	April 2010	Changed to "Released Issue"	All

TABLE OF CONTENTS

DOC	JMENT IDENTIFICATION SHEETii	
DOC	JMENT APPROVALiii	
DOC	JMENT CHANGE RECORDiv	
TABL	E OF CONTENTSv	
EXEC	CUTIVE SUMMARY1	
1.	INTRODUCTION	2
1.1	Scope	2
2.	DESCRIPTION OF THE CONTENT OF RESERVED EXPANSION FIELD	3
2.1	Length Indicator	3
2.2	Items indicator	3
2.3	TA Target Altitude	4

EXECUTIVE SUMMARY

1. INTRODUCTION

1.1 Scope

This document describes the way to encode information in the Reserved Expansion Field of ASTERIX Cat 007 (Directed Interrogations).

2. DESCRIPTION OF THE CONTENT OF RESERVED EXPANSION FIELD


2.1 Length Indicator

Definition: This field indicates the total length in octets of the Reserved

Expansion Field (including the REF length indicator itself)

Format: One-octet fixed length Data Item

Structure:



bits 8-1 (LEN) Length of REF in octets,

including the Length Indicator

itself.

Encoding Rule:

This item shall be present in every REF

2.2 Items indicator

Definition: This field indicates what are the items encoded in the REF

Format: One-octet fixed length Data Item

Structure:

Octet no. 1								
8	7	6	5	4	3	2	1	
TA	0	0	0	0	0	0	0	

bit 8 (TA) = 0 Target Altitude is not present in the REF

= 1 Target Altitude is present in

the REF

bits 7/1 Spare bits set to 0

Encoding Rule:

This item shall be present in every REF


2.3 TA Target Altitude

Definition: Potential height of a target to be interrogated. The height shall

use mean sea level as the zero reference level.

Format: Four-octet fixed length Data Item.

Structure:



Octet no. 3						Octet no. 4									
16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1
0	0							TA _{min}							LSB

bits-32/31	(spare)	Spare bits, set to 0
bits-30/17	(TA_{max})	Maximum value of potential target
		altitude

bit 17 (LSB) =25ft

bits-16/15 (spare) Spare bits, set to 0

bits-14/1 (TA_{min}) Minimum value of potential target

altitude

bit 1 (LSB) =25ft

NOTE: Negative Values are expressed in two's complement

 $TA_{min} \le TA_{max}$

Encoding Rule:

This Item is optional.

Application:

When operating a sensor on a moving platform (such as a ship) it is subjected to movements around the three special axes (heading, roll, pitch).

As shown in the diagram hereafter, the start and end value for the interrogation window differs depending on the movement of the sensor. In order to compensate for these variations, it is required to indicate to the sensor the altitude of the target in order to calculate the potential differences in the start and end angle of the interrogation window.

This REF implements the capability to indicate to the sensor the potential height band in which the target to be interrogated can be expected.

